

Datatoys Suction Mount DT-MNT-SCT

Use and Care of your Suction Mount

The **Suction Mount** is designed for non-permanent mounting to smooth and flat surfaces. It can be used inside or outside of the vehicle, on a smooth, clean, solid, glass or painted surface.

The **Suction Mount** has a standard ¼" X 20 mounting screw for fastening any camera up to 4 pounds in weight. The Mounting Arm has an approximate 180 degree adjustment, while the camera mount point has a 360 degree by 180 degree adjustment. The Camera Mount Adjusting Knob is also able to spin 360 degrees to allow for easy access when tightening.

Suction Mount Operation

1. Thoroughly clean the smooth, non-porous mounting surface (windshield, window, mirror, etc.). The surface should be dry and free of any scratches.
2. Install the camera (up to 4 pounds) onto the Mounting Screw. Make sure the rubber washer is in place below the camera. Tighten the Lock Ring firmly.
3. Loosen the Arm Adjusting Knob so the Mounting Arm moves up and down.
4. Position the Suction Cup Lever in the "down" position (as shown in the picture).
5. The mounting surface and the Suction Cup should be clean and dry. Room temperature is ideal for mounting (avoid extremes of heat and cold) and *do not moisten the Suction Cup*.
6. Position the Suction Cup in your mounting area.
7. Push the Suction Cup firmly against the mounting surface, press the Suction Cup Button and pull the Suction Cup Lever up and over the Button. You will feel the Button move out during this procedure; this action locks the Suction Cup into place.
8. Move the Mounting Arm up and down to the desired position and lock into place with the Mounting Arm Adjusting Knob.
9. Loosen the Camera Mount Adjusting Knob, position the camera, and then tighten the Camera Mount Adjusting Knob.
10. Check the direction that the camera is pointed and make sure all points are tightened.
11. To release the Suction Cup; move the Suction Cup Lever back into it's "down" position. Lift the Suction Cup Release Tab to help break the hold.



*NOTE: The suction mount is not recommended for extreme vibration, high speeds, or high g-load. It is recommended you tether any camera to the vehicle. Safe operation is the sole responsibility of the installer and Motorsports-Exchange LLC (datatoys) and its resellers take on no liability for the improper or unsafe use of the suction cup mount.